

BUILDING AND NEIGHBORHOOD COMPLIANCE DEPARTMENT (BNC) BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/building

NOTICE OF ACCEPTANCE (NOA)

TKO Doors, Inc.

N56 W24701 N. Corporate Circle

Sussex, WI 53089

SCOPE: This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County BNC -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BNC reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Model CW WL Plastic Sectional Garage Door up to 10'-0" wide APPROVAL DOCUMENT: Drawing No. 11-TKO-0001, titled "Fiberglass Dock Doors CW WL Overhead Garage Door", sheet 1 through 7 of 7, dated 04/14/11, with last revision dated 08/23/11, prepared by Engineering Express, signed and sealed by Frank L. Bennardo, P.E., bearing the Miami-Dade County Product Control approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: A permanent label with the manufacturer's name or logo, manufacturing address, model number, the positive and negative design pressure rating, indicate impact rated if applicable, installation instruction drawing reference number, approval number (NOA), the applicable test standards, and the statement reading 'Miami-Dade County Product Control Approved' is to be located on the door's side track, bottom angle, or inner surface of a panel.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Carlos M. Utrera, P.E.

MIAMI-DADE COUNTY
APPROVED

109/06/11

NOA No 11-0513.04 Expiration Date: September 15, 2016 Approval Date: September 15, 2011

Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

Drawing No. 11-TKO-0001, titled "Fiberglass Dock Doors CW WL Overhead Garage Door", sheet 1 through 7 of 7, dated 04/14/11, with last revision dated 08/23/11, prepared by Engineering Express, signed and sealed by Frank L. Bennardo, P.E.

B. TESTS

- 1. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 2) Large Missile Impact Test per FBC, TAS 201-94
 - 3) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 4) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

Along with marked-up drawings and installation diagram of Series/Model CW WL, dock door, prepared by Architectural Testing, Inc., Test Report No. 98517.01-602-18, dated 03/24/10, signed and sealed by Joseph A. Reed, P.E.

- 2. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 2) Large Missile Impact Test per FBC, TAS 201-94
 - 3) Cyclic Wind Pressure Loading per FBC, TAS 203-94

Along with marked-up drawings and installation diagram of Series/Model CW WL, dock door, prepared by Architectural Testing, Inc., Test Report No. 89514.01-602-18, dated 04/24/09, signed and sealed by Joseph A. Reed, P.E.

- 3. Test report on Accelerated Weathering using Xenon Arc Light Apparatus for 4500 hours, per ASTM G155-04 and on Tensile Test per ASTM D638 of FRP composite panels, prepared by Architectural Testing, Inc., Test Report No. A3696.01-106-18, dated 05/04/11, signed and sealed by Joseph A. Reed, P.E.
- Test report on Self-ignition Temperature per ASTM D1929-96(2000)e1 of various plastic and fiberglass door components, prepared by Architectural Testing, Inc., Test Report No. 95487.01-106-31, dated 11/04/09, signed and sealed by Joseph A. Reed, P.E.
- 5. Test report on Smoke Density Rating per ASTM D2843-99(2004) of different types of plastics, prepared by Architectural Testing, Inc., Test Report No. 92103.01-106-18, dated 05/04/11, signed and sealed by Joseph A. Reed, P.E.
- 6. Test report on Smoke Density Rating per ASTM D2843-99(2004) of vinyl and seals, prepared by Architectural Testing, Inc., Test Report No. 95487.02-106-31, dated 11/04/09, signed and sealed by Joseph A. Reed, P.E.

Carlos M. Utrera, P.E.

Product Control Examiner NOA No 11-0513.04

Expiration Date: September 15, 2016 Approval Date: September 15, 2011

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

B. TESTS (CONTINUED)

- 7. Test report on Rate of Burn per ASTM D635-06 of different types of plastics, prepared by Architectural Testing, Inc., Test Report No. 92103.02-106-18, dated 08/19/09, signed and sealed by Joseph A. Reed, P.E.
- 8. Test report on Rate of Burn per ASTM D635-06 of vinyl and seals, prepared by Architectural Testing, Inc., Test Report No. 95487.03-106-31, dated 11/04/09, signed and sealed by Joseph A. Reed, P.E.

C. CALCULATIONS

1. Jamb anchor calculations, complying with FBC-2007, prepared by Engineering Express, dated 04/15/11, signed and sealed by Frank L. Bennardo, P.E.

D. QUALITY ASSURANCE

1. Miami-Dade Building and Neighborhood Compliance Department (BNC)

E. MATERIAL CERTIFICATIONS

1. Test report on Self-Ignition Temperature per ASTM D1929-96(2000), Flame Spread Index and Smoke Developed Index per ASTM D84-10b of RayLite EPS foam insulation, prepared by Architectural Testing, Inc., Test Report No. B1755.01-122-18, dated 08/17/11, signed and sealed by Michael D. Stremmel, P.E.


F. STATEMENTS

- 1. Statement letter of code conformance with 2007 FBC, issued by Engineering Express, dated 04/18/11, signed and sealed by Frank L. Bennardo, P.E.
- 2. Statement letter of no financial interest issued by Engineering Express, dated 04/18/11, signed and sealed by Frank L. Bennardo, P.E.


Carlos M. Utrera, P.E. Product Control Examiner


NOA No 11-0513.04


Expiration Date: September 15, 2016 Approval Date: September 15, 2011





11-TKO-0001











MATERIALS LIST:

S
W.

Part Number	Item Description	Manufacturer/Notes	Location	ightharpoonup
Panel Components				_
20-00090	0.125" interior skin	Extruded Polyethylene sheet	Front face of all panels	
20-00084	0.125" interior skin	Polycarbonate sheet	Front face of all panels (alternative material)	
20-01713	0.125" exterior skin	Pultruded Fiberglass sheet†	Back face of all panels	
20-00125	1-1/2" insulation	11b. density E.P.S. sheet	Inside core of all panels	
20-01718	1-1/2" SQ x 0.125" wall tube [horizontal]	Pultruded Fiberglass tube	Top/bottom of all panel frames	
20-01721	1-1/2" SQ x 0.125" wall tube [vertical]	Pultruded Fiberglass tube	Sides of all panels frames	
20-00001	Corner tube bracket	0.119 steel	Corners of all panel frames	
20-00008	Panel spacer	HMPE plastic	Top corners of all panels forming panel joint	\neg
20-01679	"D" profile weather stripping	Sponge rubber	Top of all panels forming panel joint	
20-00132	Panel Side seal	22 oz. Vinyl	Sides of all non- bottom panel frames	$\overline{}$
20-00212	Bottom Panel Side seal	22 oz. Vinyl	Sides of all bottom panel frames	\neg
20-00330	Bottom seal	35 oz. Hypalon	Bottom panel	\dashv
Panel Hardware	· · · · · · · · · · · · · · · · · · ·		<u></u>	
30-00676	FIXED plunger assembly	TKO Doors (steel)	1 at each upper corner of 3rd panel & above	
20-01459	Plunger Covers	TKO Doors (steel)	1 each per plunger	\neg
30-00589	4" Porthole Assembly	TKO Doors	1 in center of 3rd panel	\dashv
20-00644	Panel Plate	Galv 12-ga steel	Sides of all panels	
30-00673	Fabric Hinge Assembly	40 oz. Vinyl polyester (2 layer)	Top corners of all panels forming panel joint	_
20-01605	Fabric Center hinge	40 oz. Vinyl polyester (2 layer)	Top center of all panels forming panel joint	\dashv
20-00015	Hinge strap	TKO Doors (steel)	1 each for corner hinges 2 each for center hinges	\dashv
20-01604	Hinge Wire	TKO Doors (steel)	1 each per corner hinges 30-00673	_
30-00643	SPRING plunger assembly	TKO Doors (steel) [6 per door]	1 at each upper/lower corner of bottom panel & 1 at each upper corner on 2nd panel	\dashv
20-01344	Plate, Adapter	Galv. 12 ga. Steel	Under each Spring Plunger 30-00643 except where handles 20-00613 are located	\dashv
30-00004	Slide lock assembly	TKO Doors (steel) [4 per panel]	2 each on each end centered on panel	\dashv
30-00590	Knock Out Lock, Windload	TKO Doors (steel)	1 per slide lock. (out hole of engaged lock)	
20-00613	Handle	TKO Doors (steel)	Lower corners of bottom panel &	
20-00013	<u> </u>	TKO Doors (steel)	Top corners of top panel	-
	TPU cable bracket (optional)		Cable Attachment Point [varies]	
20-00295	Bracket, Clevis [optional]	TKO Doors[steel]		\dashv
20-01609	Panel seal	40 oz. Vinyl polyester	Between all panels forming panel joint (2 per)	
Track Hardware	IW WO . 1 /1	I II D AND DA	T	\dashv
20-00582	UW SKO track (length varies with door size)	UHMWPE*	Lower track	\dashv
20-00586	UW 12" transition, R.H.	UHMWPE*	Lower track	-
20-00587	UW 12" transition, L.H.	UHMWPE*	Lower track	
20-00183	UW strt track (length varies with door size)	UHMWPE*	Upper track	\dashv
20-00603	Splice Channel (optional based on upper track)	Galv 8-ga steel	Lower track	
20-00564	UW universal steel (length varies with door size)	Galv 8-ga steel	Lower track	
Fasteners	M44 10 2 150 11 11 11 11 11 11 11 11 11 11 11 11 11			
10-00043	5/16-18 x 2-1/2" ribneck bolt	****	4 per panel corner (12 per panel)	
10-00007	5/16-18 flange nut	****	4 per panel corner (12 per panel)	\dashv
10-00145	1/4-20 x 2-1/4" ribneck bolt	****	1 per vertical panel edge (centered) & min 12" O.C. per horizontal edge	\rightarrow
10-00065	1/4 Washer	****	1 per vertical panel edge (centered) & min 12" O.C. per horizontal edge	_
10-00005	1/4-20 flange nut	****	1 per vertical panel edge (centered) & min 12" O.C. per horizontal edge	_
10-00061	#8 x 3/4" tek screw	****	2 per panel spacer	
10-00062	#14 x 3/4" tek screw	****	4 per slide lock assembly, 2 per Spring Plungers where applicable	
10-00046	5/16-18 X 2-1/2" PFH screw	****	Min 12" O.C. per track length	^
10-00007	5/16-18 flange nut	****	Min 12" O.C. per track length	D: X
10-00288	Plate, Truss, Connector 1" x 4"	****	1" above each fastener in lower track	
10-00289	Plate, Truss, Connector 2" x 4"	****	Aligned with the bottom edge of lower track mounting surface	_ >

*ULTRA HIGH MOLECULAR WEIGHT POLYETHYLENE

TKO DOCK DOORS

11-TKO-0001
SCALE: 02
PAGE DESCRIPTION:

7